
INDIVIDUALLY CONFIGURABLE.

We offer you expansion systems (Plus modules) in various sizes to add on to your StoreManager Master system.



StoreManager^{START} 717 Plus

- Footprint 717 x 725 mm ($\leq 0.6 \, \text{m}^2$)
- This expansion system has the same length and width as the StoreManager^{START} Master.
 Turn to page 29 for the possible number and size of electronically locked drawers and compartments.

The following heights (outer dimensions) are available: 800 mm, 950 mm, 1,100 mm, 1,250 mm, 1,550 mm





StoreManagerSTART 1023 Plus

- Footprint 1,023 x 725 mm (≤ 0.8 m²)
- This expansion system is wider than the StoreManager^{START} 717, but it can only be equipped with electronically locked drawers without individual compartments.

The following heights (outer dimensions) are available: 800 mm, 950 mm, 1,100 mm, 1,550 mm



Dimensions

Width

De pth

Height

Footprint

Weight empty

Drawer/compartment dimensions $w \times d \times drawer$ height

No compartments

4 compartments

6 compartments

8 compartments

12 compartments

16 compartments

Drawer height

75 mm

100 mm

150 mm

200 mm

250 mm

300 mm

General

Max. load per drawer

Max. access time

Power supply

Operation

Network connection

Permissible temperature in operation

Permissible humidity

Maintenance

Dust-protected

Do you want to know more? Simply write to us at: storemanager@arno.de







StoreManager ^{START} 717 Master	StoreManager ^{START} 717 Plus	StoreManager ^{START} 1023 Plus
717 mm	717 mm	1,023 mm
725 mm	725 mm	725 mm
1,600 mm	800 mm / 950 mm / 1,100 mm / 1,250 mm / 1,550 mm	800 mm / 950 mm / 1,100 mm / 1,550 mm
$\leq 0.6 \text{ m}^2$	$\leq 0.6 \text{m}^2$	$\leq 0.8 \text{ m}^2$
Depending on configuration	Depending on configuration	Depending on configuration
612×612 mm	612×612 mm	918×612 mm
594×111 mm / 296×260 mm	594×111 mm / 296×260 mm	-
594×62 mm	594×62 mm	-
296×111 mm	296×111 mm	-
98×260 mm	98×260 mm	-
147×111 mm	147×111 mm	-
1 / 6 / 8 / 12 / 16 compartments	1 / 6 / 8 / 12 / 16 compartments	Only available without individual compartments
1 / 4 / 8 / 12 / 16 compartments	1 / 4 / 8 / 12 / 16 compartments	Only available without individual compartments
1/4/8/16 compartments	1/4/8/16 compartments	Only available without individual compartments
Only available without individual compartments	Only available without individual compartments	Only available without individual compartments
Only available without individual compartments	Only available without individual compartments	Only available without individual compartments
Only available without individual compartments	Only available without individual compartments	Only available without individual compartments
 200 kg	200 kg	200 kg
2 seconds	2 seconds	2 seconds
230 volts / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Touch screen, barcode scanner	-	-
LAN socket	via Master module	via Master module
+10 °C to +40 °C	+10°C to +40°C	+10 °C to +40 °C
5 – 95% (non-condensing)	5 – 95% (non-condensing)	5 – 95% (non-condensing)
Hardware fully maintenance-free	Hardware fully maintenance-free	Hardware fully maintenance-free
Yes	Yes	Yes
		· · · · · · · · · · · · · · · · · · ·